

LIQUID RELEASE

LIQUID STAMPING RELEASE AGENT

QUICK FACTS

PRODUCT NAME	LIQUID RELEASE
PACKAGING	5-GALLON (18.9 L) pail
COVERAGE	Approx. 240 ft ² per gallon (5.9 m ² /L)
APPEARANCE	Clear
ODOR	Bubblegum
VOC CONTENT	0 g/L
SHELF LIFE	Under normal conditions: when kept dry and moisture free, out of direct sunlight, the shelf life of an unopened container is (12) months from the date of purchase. Storage must be under rood and off the floor. Avoid temperature extremes. Rotate inventory to maintain product is within limits.
MANUFACTURER PART #	SKU #

DESCRIPTION

Liquid Release is a colorless, bubblegum scented petroleum distillate formula to release any decorative imprinting tool from concrete or polymer modified cementitious topping. Liquid Release provides a lubricating barrier that protects and prolongs the life of stamping tools and evaporates from the cementitious surface leaving minimal residue.

USES

Specifically designed for use in conjunction with stamped concrete, stamped overlay, texture systems and imprinting, stamp tools. May be used on interior or exterior surfaces. It is recommended the use of Liquid Release for projects that are to be textured, but colored later, e.g stamp overlay and stamp concrete. Excessive masking associated with messy powder release is virtually eliminated with Liquid Release.

APPLICATION

Application of Liquid Release is accomplished through misting the cementitious surface with a pump-up sprayer. Imprinting tools must have their texture face saturated at the start of stamping.

Apply only as much release as can be covered with tools in a few minutes in temperatures above 40°F and rising. Direct sunlight and windy conditions will accelerate the evaporative properties of Liquid Release.



CLEAN-UP

Before Liquid Release dries; spills and tools can be cleaned up with water.

DISPOSAL

Contact your local government household hazardous waste coordinator for information on disposal of unused product.

LIMITATIONS

For use by trained professionals that have read the complete SDS.

WARNING

KEEP OUT OF REACH OF CHILDREN. Inhalation:

Avoid prolonged breathing of airborne dust, particularly present during mixing. Use NIOSH approved respirator for nuisance if threshold limit values are unsafe. Skin Contact: Skin contact may cause irritation. Remove contaminated clothing and wash affected skin with soap and water.

Launder clothing before reuse. If symptoms persist, seek medical attention. Eyes: Wear safety eye protection when applying. Contact with eyes may cause irritation. Flush eyes with water for 15 minutes. If symptoms persist, seek medical attention.

WARRANTY

Warranty of this product, when used according to the directions, is limited to refund of purchase price or replacement of product (if defective), at manufacturers' or seller's option. Concrete Genetics shall not be liable for the cost of labor or direct and/or incidental consequential damages.